

## **SPECIFY DCM SURFACES RESIN BOUND GRAVEL**

Q23 Gravel/ Hoggin/ Woodchip/ Resin Bound Roads/ Pavings/ Overlays

### **SURFACE COURSE**

- Porous Decorative Bound Gravel Surfacing.
- Flexible and crack resistant
- Binder: Fully coated with a flexible resin
- Chippings: Minimum blend of three aggregate particles
- Aggregate size: 6mm.

### **BUILD UP**

16-24mm thickness, depending on product usage

### **BINDER COURSE:**

50mm depth AC 14 Open Texture Binder

### **GRANULAR SUB-BASE:**

100-300mm well compacted, nonfrost susceptible Type 1/3 sub-base, dependent on conditions.  
Geotextile: Sheet

### **APPLICATION**

- Cold applied. Hand applied and trowelled.
- Thoroughly mixed and uniformly spread.

### **LAYING GENERALLY**

- Channels, gullies, etc: Keep clear.
- Finished surfaces:
  - Lines and levels: To prevent ponding.
  - Overall texture: Even.
  - State at completion: Clean.

### **Other requirements:**

- To manufacturers details and sub base design
- To be installed by manufacturer approved installer, utilising manufacturers recommended details
- BBA certified product

### **MANUFACTURER**

Product reference: Resin Bound Gravel  
Manufacturer: DCM Surfaces  
Address Wigan Road, Leyland, PR25 5XW  
Telephone: 01772 440340  
Email: [info@dcmsurfaces.com](mailto:info@dcmsurfaces.com)  
Website: [www.dcmsurfaces.com](http://www.dcmsurfaces.com)

### **PROJECT DETAILS**

Area Size (m2): XX  
Colour: XX