

BONDED GRAVEL

...for walkways, footpaths, landscapes and courtyards

Resin Bonded Gravel is non-permeable, meaning water does not drain through. The rough texture gives the surface anti-slip qualities as well as a natural appearance, making it a National Trust favourite.

Bonded Gravel is applied by scattering stone gravel onto a resin base. The aggregate is available in a range of colours which can be used to match exterior features.

“ I would recommend DCM to anyone considering having their drive resurfaced. We experienced consistently high standards in the service levels, from start to completion.

DCM were not the cheapest quote we received, nor the most expensive, but after checking with several DCM customers, we were happy that they were offering the best value for money.

Our drive was the final part of an 18-month new build project, and DCM were one of the most professional organisations we had dealings with.

Homeowner, Prestbury

”

**Terms and Conditions apply

T. +44 (0)1772 440340 E. info@dcmsurfaces.com

WWW.DCMSURFACES.COM

Key Specifications

- 5 year warranty**
- Mimics the appearance of loose gravel
- Rough texture for a natural appearance and slip resistance
- Visually appealing
- Non-Permeable

RECOMMENDED BUILD UP:



3mm resin bonded gravel *

25mm AC6 dense surface course macadam
50mm AC 20/14 dense binder course macadam
(laid 30 days prior to gravel install)

Min 100mm MOT type 1 dependent
on ground conditions

Geotextile membrane

Edge options: Rubber, Concrete,
Aluminium

*Any deviations will show if the surface is
not completely levelled.

BONDED GRAVEL

BONDED GRAVEL



Autumn Quartz



Red Granite



Chinese Grey Bauxite



Chinese Buff Bauxite



Brittany Bronze



Silver Grey Granite



White




Pearl Quartz



Beige and Cream



Staffordshire Pink



Green Granite



Black Granite

*Additional colours available on request

Base

The base must be dry and of sound construction.

SURFACE DEPTH	CONCRETE	MACADAM	CONIPAVE	FLAGS	SOIL / GRASS	MOT TYPE 1
3-5mm	✓	✓	✗	✗	✗	✗

Bonded Gravel Technical Data

TECHNICAL DATA	VALUE
Material	3mm natural aggregate, bonded onto resin.
Curing Period	4 hours - Pedestrian Use 24 hours - Vehicle Use (weather dependent)

