

SPECIFY DCM SURFACES RESIN BOUND GRAVEL

Q23 Gravel/ Hoggin/ Woodchip/ Resin Bound Roads/ Pavings/ Overlays

SURFACE COURSE

- Porous Decorative Bound Gravel Surfacing.
- Flexible and crack resistant
- Binder: Fully coated with a flexible resin
- Chippings: Minimum blend of three aggregate particles
- Aggregate size: 6mm.

BUILD UP

16-24mm thickness, depending on product usage

BINDER COURSE:

50-80mm depth AC 14 Open Texture Binder, dependent on site

GRANULAR SUB-BASE:

100-300mm well compacted, nonfrost susceptible Type 1/3 sub-base, dependent on conditions.
Geotextile: Sheet

APPLICATION

- Cold applied. Hand applied and trowelled.
- Thoroughly mixed and uniformly spread.

LAYING GENERALLY

- Channels, gullies, etc: Keep clear.
- Finished surfaces:
 - Lines and levels: To prevent ponding.
 - Overall texture: Even.
 - State at completion: Clean.

Other requirements:

- To manufacturers details and sub base design
- To be installed by manufacturer approved installer, utilising manufacturers recommended details
- BBA certified product

MANUFACTURER

Product reference: Resin Bound Gravel
Manufacturer: DCM Surfaces
Address Wigan Road, Leyland, PR25 5XW
Telephone: 01772 440340
Email: info@dcmsurfaces.com
Website: www.dcmsurfaces.com

PROJECT DETAILS

Area Size (m2): XX
Colour: XX