

# SELF BINDING GRAVEL

...for walkways, footpaths, landscapes

Self-binding gravel is an easy to lay alternative to traditional materials such as flags, paving, macadam or concrete.

Soft and natural in appearance, it can be seen at some of the country's most prestigious stately homes and enhances many of the most beautiful National Trust and English Heritage gardens.

The gravel binds together when rolled to provide a self compacted surface which remains firmer underfoot than conventional loose aggregate. This makes the surface an ideal choice not only for pedestrian and vehicular use, but also for cycleways, bridle paths, and golf courses.



We have been using DCM Surfaces for many years now and always find the team to be very knowledgeable, professional and willing to go the extra mile to ensure the job is completed to a very high standard within the set time.

Managing Director, HAGS



## Key Specifications

- Complements either modern day or historical surroundings
- Non-slip, non-trip surface
- More aesthetically pleasing than concrete or asphalt
- Safer than paving slabs which often dislodge and loosen over time

## RECOMMENDED BUILD UP:



Min 50mm Self-binding gravel\*

Min 50-100mm MOT Type 1 20mm to dust (non-recycled). Laid, level and compacted to the required tolerance.

Geotextile membrane

Edge options: Rubber, Concrete, Aluminium

\*Standard build up. Depths may vary depending on use / sub-base.

\* Can't be used for xx days

\*\*Terms and Conditions apply

T. +44 (0)1772 440340 E. [info@dcmsurfaces.com](mailto:info@dcmsurfaces.com)

[WWW.DCMSURFACES.COM](http://WWW.DCMSURFACES.COM)



# SELF BINDING GRAVEL

## Base

The base must be dry and of sound construction.

SURFACE DEPTH	CONCRETE	MACADAM	WETPOUR	FLAGS	SOIL / GRASS	MOT TYPE 1
50mm Pathways	X	X	X	X	X	✓
100mm Driveways	X	X	X	X	X	✓

## Technical Data

TECHNICAL DATA	VALUE
Material	Dolomitic Limestone
Curing Period	The surface is ready to use once dry

